



### **Product technical sheet**

# **MINISWEET 0108-2**







1 - 8 years

19 kids

24,9 m<sup>2</sup>



### **Material specification**

- Stainless steel, hot-dip galvanized and powder coated or powder galvanized and powder coated steel construction of 80 x 80 cm profile,
- Roofs, side panels made of durable HDPE or HPL plate, resistant to weather conditions,
- Windows made of polycarbonate,
- Educational paneles and moving elements made of HDPE or HPL plate, resistant to weather conditions,
- · Spherical windows made of polycarbonate,
- Double wall tube passage made of polypropylene,
- Screws covered with plastic caps and/or stainless steel screws,
- Safe end caps on top of the structure made of rubber or polypropylene,



### **Facilitating disability**



easy access



shelters





#### Intellectual development



sensory

thinking



sight



### Physical development



hiding



crawling






















### **Product technical sheet**

## MINISWEET 0108-2

#### **Product data**

Length	303 cm	
Width	158 cm	
Total height	168 cm	
Age group	1 - 8 years	
Number of users	19 kids	
Safety zone	24,9 m2	
Free fall height	< 60 cm	
In accordance with norm EN	1176-1:2017	
Weight of the heaviest part	12 kg	
Dimensions of the largest part	178x15x15 cm	
Availability of spare parts	YES	
Installation time	7,5 h	
Color options		

Data is subject to change without prior notice.

### Additional information

- equipment adapted for the disabled; intended for public playgrounds;
- equipment has a certificate issued by an accredited entity or a declaration of conformity;
- no sharp edges or chinks that would pose a danger of jimming the head, fingers or any other body parts;
- anchoring on flat surface, 80/70/60 cm deep;
- render is for reference only, the actual appearance of the equipment and its color may vary;

### **Guarantee**



30 year guarantee -Structural strength of steel and stainless steel components



15 year guarantee -Structural failure of steel and stainless steel, for dynamic equipment



10 year guarantee - Structural failure of high density polyethylene and high pressure laminates components



5 year guarantee - Corrosion of stainless steel and hot dip galvanized and powder coated components; against bark beetles and rot in case of wooden structural elements

Detailed information in the guarantee card

Vinci Group Sp. z o.o. Seminaryjna 9 Street 99-400 Łowicz

VAT: 534-250-14-46 PHONE: +48 42 203 24 99 ext. 26 M: +48 793 404 991





### Surfaces according to EN 1176-1:2017

	Description (mm)	Layer thickness (cm)	Maximum fall heights (cm)
Turf/ top layer of soil (A,B,C)	-	-	≤100
hark (A.C.)	Particle size from 20 to 80 40	≤200	
Dark (A,C)		40	≤300
woodchips (A,C)	Particle size from 5 to 30	30	≤200
		40	≤300
sand or gravel (A,C)	Particle size from 0,25 to 8	30	≤200
		40	≤300
synthetic attested (A,B,C)	Tested according to EN 1177		60

### **Product technical sheet**

# **MINISWEET 0108-2**

Amount of safe surface corresponding with free fall height:

HIC <60 24,9 m<sup>2</sup>

Data is subject to change without prior notice.

